



PA2-KIT

PA2-KIT is an accessory package for FANVIL SIP Intercom/Paging Gateway PA2. It includes IP camera module, speaker module, microphone module and button module. You can quickly build high quality audio/video intercom equipment by PA2-KIT, eliminating the components selection, matching test and reliability test cumbersome process.



PA2



Camera



MIC



Speaker






Button & LED

PA2-KIT

Highlights

- ☑ High reliability components, plug and play
- ☑ 720P camera module to achieve HD video call; The lens mounting height and Angle can be adjusted to meet the requirements of various scenarios
- ☑ High sensitivity pick up, waterproof, dustproof designed microphone module, suitable for harsh environment application
- ☑ 5W/8Ω speaker module, satisfied the noisy environment to the demand of the high loudness of the intercom equipment
- ☑ Waterproof and dustproof designed stainless steel button with LED indicator for better operation

| Component | Photo | Functions | Features |
|------------|---|---|--|
| Speaker |  | <ul style="list-style-type: none"> - Speaker with self-adhesive layer. - Module with dustproof, waterproof protective film. - 5W/8Ω Waterproof loudspeaker. | 5W/8Ω Waterproof loudspeaker, The diameter of the horn is 57mm, and 13.7mm high. Include 150cm Shielding wire. |
| Microphone |  | <ul style="list-style-type: none"> - Microphone with self-adhesive layer. - Module with dustproof, waterproof protective film. - The sensitivity of microphone is -38dB±2. | Sensitivity:-38dB±2, Standard working voltage:3V, the maximum working voltage is 10V, Output impedance≤2.2KΩ, Diameter of the microphone is 9.7mm and the height is 4.7mm. Include 150cm Shielding wire. |
| Button |  | <ul style="list-style-type: none"> - Stainless steel button with backlight. - Protect level IP67, IK10. - The mechanical lifetime of the button is 200,000 times. - LED lamp lifetime is 400,000 hours. | The diameter of the button is 16mm, and the height is 23.8mm. The button is self-restorable stainless steel button with 150cm shielding wire. |
| IP Camera |  | <ul style="list-style-type: none"> - Module with self-adhesive layer. - 720P HD camera, support dual video stream. - Power by PA2 LAN Port (12V DC) - Wide angle lens, the installation angle can be fine tuned. <p>NOTE: Do not connect the PoE injector /switch directly using this camera module. It will be damaged.</p> | 1.0M 1/4" H62 CMOS sensor , color 0.1Lux@F1.2, black/white 0.01Lux@F1.2. H.264, support dual stream, AVI; Main stream:1280*720; sub-stream: 704*576; |

The above specifications may be updated in the future without prior notice. All hardware/software/physical features should be based on the final shipped products.

For more information, please visit : www.fanvil.com

Compatibility List:



www.fanvil.com

Add: 4F, Block A, Building 1#, GaoXinQi Hi-Tech Park (Phase-II), 67th District, Bao'An, Shenzhen, China 518101

Tel: +86-755-2640-2199 Fax: +86-755-2640-2618 Email: sales@fanvil.com

